



class

GTK::V3::Gtk::GtkComboBoxText

Table of Contents

- 0.1 [GtkComboBoxText — A simple, text-only combo box](#)
- 1 [Synopsis](#)
- 2 [Methods](#)
- 2.1 [gtk_combo_box_text_append](#)
- 2.2 [gtk_combo_box_text_prepend](#)
- 2.3 [gtk_combo_box_text_insert](#)
- 2.4 [\[gtk_combo_box_text_\] append_text](#)
- 2.5 [\[gtk_combo_box_text_\] prepend_text](#)
- 2.6 [\[gtk_combo_box_text_\] insert_text](#)
- 2.7 [gtk_combo_box_text_remove](#)
- 2.8 [\[gtk_combo_box_text_\] remove_all](#)
- 2.9 [gtk_combo_box_text_get_active_text](#)
- 2.10 [new](#)

```
unit class GTK::V3::Gtk::GtkComboBoxText;  
also is GTK::V3::Gtk::GtkComboBox;
```

GtkComboBoxText — A simple, text-only combo box

Synopsis

```
# Get a fully designed text combobox  
my GTK::V3::Gtk::GtkComboBoxText $server-cb .= new(:build-id<serverComboBox>);  
my Str $server = $server-cb.get-active-id;
```

Methods

gtk_combo_box_text_append

```
method gtk_combo_box_text_append ( Str $id, Str $text )
```

Appends text. See also [gnome developer docs](#).

gtk_combo_box_text_prepend

```
method gtk_combo_box_text_prepend ( Str $id, Str $text )
```

Prepends text. See also [gnome developer docs](#).

This is the same as calling `gtk_combo_box_text_insert()` with a position of 0.

gtk_combo_box_text_insert

```
method gtk_combo_box_text_insert ( Int $position, Str $id, Str $text )
```

Insert text at position. See also [gnome developer docs](#).

[gtk_combo_box_text_] append_text

```
method gtk_combo_box_text_append_text ( Str $text )
```

Append text. See also [gnome developer docs](#).

[gtk_combo_box_text_] prepend_text

```
method gtk_combo_box_text_prepend_text ( Str $text )
```

Prepend text. See also [gnome developer docs](#).

[gtk_combo_box_text_] insert_text

```
method gtk_combo_box_text_insert_text ( int32 $position, Str $text )
```

Insert text at position. See also [gnome developer docs](#).

gtk_combo_box_text_remove

```
method gtk_combo_box_text_remove ( Int $position )
```

Remove text at position. See also [gnome developer docs](#).

[gtk_combo_box_text_] remove_all

```
method gtk_combo_box_text_remove_all ( )
```

Remove all text entries. See also [gnome developer docs](#).

gtk_combo_box_text_get_active_text

```
method gtk_combo_box_text_get_active_text ( )
```

Get selected entry. See also [gnome developer docs](#).

new

```
multi submethod BUILD ( :$widget! )
```

Create a simple text combobox using a native object from elsewhere. See also `Gtk::V3::Glib::GObject`.

```
multi submethod BUILD ( Str :$build-id! )
```

Create a simple text combobox using a native object from a builder. See also `Gtk::V3::Glib::GObject`.

Generated using Pod::Render, Pod::To::HTML, Camelia™ (butterfly) is © 2009 by Larry Wall