       The application/smil and application/smil+xml Media Types

Status of This Memo

Copyright Notice

Abstract

   This document specifies the media type for versions 1.0, 2.0, and 2.1
   of the Synchronized Multimedia Integration Language (SMIL 1.0, SMIL
   2.0, SMIL 2.1). SMIL allows integration of a set of independent
   multimedia objects into a synchronized multimedia presentation.

1. Introduction

   The World Wide Web Consortium (W3C) has issued specifications that
   define versions 1.0 [1], 2.0 [2] and 2.1 [3] of the Synchronized
   Multimedia Integration Language (SMIL). This memo provides
   information about the application/smil and application/smil+xml media
   types.

   The definition is based on RFC 3023, which defines the use of the
   "application/xml" media type [4]. Before using the
   "application/smil" or "application/smil+xml" media type, implementors
   must thus be familiar with [4].

2. Synchronized Multimedia Integration Language

   SMIL allows integrating a set of independent multimedia objects into
   a synchronized multimedia presentation. Using SMIL, an author can

   1. describe the temporal behavior of the presentation,
   2. describe the layout of the presentation on a screen,
   3. associate hyperlinks with media objects, and
   4. define conditional content inclusion/exclusion based on
      system/network properties.

3. Registration Information

3.1. Registration of MIME media type application/smil

   MIME media type name: application

   MIME subtype name: smil

   Required parameters: none

   Optional parameters:

      charset

         Same as charset parameter considerations of application/xml in
         RFC 3023.

      profile

         See Section 5 of this document.

   Encoding considerations:

      Same as encoding considerations of application/xml in RFC 3023

   Security considerations: See Section 6, "Security Considerations", of
   this document.

   Interoperability considerations:

      SMIL documents contain links to other media objects. The SMIL
      player must be able to decode the media types of these media in
      order to display the whole document. To increase
      interoperability, SMIL has provisions for including alternate
      versions of a media object in a document.

   Published specification: See [1], [2], and [3]

   Applications which use this media type:

      SMIL players and editors

Additional information:

Semantics of fragment identifiers in URIs: The SMIL media type
allows a fragment identifier to be appended to a URI pointing to a
SMIL resource (e.g., http://www.example.com/test.smil#foo). The
semantics of fragment identifiers for SMIL resources are defined
in the SMIL specification.

Magic number(s):

There is no single initial byte sequence that is always present
for SMIL files. However, Section 4 of this document gives some
guidelines for recognizing SMIL files.

File extension(s): .smil, .smi, .sml

NOTE: On the Windows operating system and the Macintosh platform, the
".smi" extension is used by other formats. To avoid conflicts, it is
thus recommended to use the extension ".smil" for storing SMIL files
on these platforms.

Macintosh File Type Code(s): "TEXT", ".SMI", "SMIL"

Object Identifier(s) or OID(s): none

Person & email address to contact for further information:

The author of this memo.

Intended usage: OBSOLETE

Author/Change controller:

The SMIL specification is a work product of the World Wide Web
Consortium's SYMM Working Group.

The W3C has change control over the specification.

3.2. Registration of MIME media type application/smil+xml

   MIME media type name: application

   MIME subtype name: smil+xml

   Required parameters: See registration of application/smil.

   Optional parameters: See registration of application/smil.

   Encoding considerations: See registration of application/smil.

   Security considerations: See Section 6, "Security Considerations", of
   this document

   Interoperability considerations: See registration of
   application/smil.

   Published specification: See registration of application/smil.

   Applications which use this media type: See registration of
   application/smil.

   Additional information: See registration of application/smil.

   Magic number(s): See registration of application/smil.

   File extension(s): See registration of application/smil.

   Macintosh File Type Code(s): See registration of application/smil.

   Object Identifier(s) or OID(s): See registration of application/smil.

   Person & email address to contact for further information: See
   registration of application/smil.

   Intended usage: COMMON

   Author/Change controller: See registration of application/smil.

4. Recognizing SMIL Files

   All SMIL files will have the string "<smil" near the beginning of the
   file. Some will also begin with an XML declaration that begins with
   "<?xml", though that alone does not indicate a SMIL document.

   All SMIL 2.0 files must include a declaration of the SMIL 2.0
   namespace. This should appear shortly after the string "<smil", and
   should read 'xmlns="http://www.w3.org/2001/SMIL20/Language"'.

   All SMIL 2.1 files must include a declaration of a SMIL 2.1
   namespace, appearing shortly after the string "<smil". The namespace
   string depends on the language profile. Please refer to the SMIL 2.1
   specification for the definition of the relevant namespace names.

5. The "profile" Optional Parameter

   This parameter is meant to be used in MIME media-type-based content
   negotiation (such as that done with the HTTP "Accept" header) to
   negotiate for a variety of SMIL-based languages. It is modelled
   after the "profile" parameter in the application/xhtml+xml MIME type
   registration [5] and is motivated by very similar considerations.

   The parameter is intended to be used only during content negotiation.
   It is not expected that it be used to deliver content, or that origin
   web servers have any knowledge of it (though they are welcome to).
   It is primarily targeted for use on the network by proxies in the
   HTTP chain that manipulate data formats (such as transcoders).

   The value of the profile attribute is a URI that can be used as a
   name to identify a language. Though the URI need not be resolved in
   order to be useful as a name, it could be a namespace, schema, or
   language specification.

   For example, user agents supporting only SMIL Basic (see
   http://www.w3.org/TR/smil20/smil-basic.html) currently have no
   standard means to convey their inability to fully support SMIL 2.0.
   While SMIL 2.0 Basic user agents are required to parse the full SMIL
   2.0 language, there is potentially a substantial burden in receiving
   and parsing document content that will not be presented to the user,
   since its functionality is not included in SMIL Basic.

   In the future, the functionality afforded by this parameter will also
   be achievable by the emerging work on a protocol to transfer
   Composite Capability/Preferences Profiles (CC/PP) descriptions [6].
   It is suggested that the "profile" parameter be used until the CC/PP
   protocol work has been finalized.

An example use of this parameter as part of a HTTP GET transaction
would be:

        Accept: application/smil+xml;
            profile="http://www.w3.org/2001/SMIL20/HostLanguage"

6. Security Considerations

   SMIL documents contain a construct that allows "infinite loops".
   This is indispensable for a multimedia format. However, SMIL clients
   should foresee provisions such as a "stop" button that lets users
   interrupt such an "infinite loop".

   As with HTML, SMIL documents contain links to other media (images,
   sounds, videos, text, etc.), and those links are typically followed
   automatically by software, resulting in the transfer of files without
   the explicit request of the user for each one. The security
   considerations of each linked file are those of the individual
   registered types.

   The SMIL language contains "switch" elements. SMIL provides no
   mechanism that ensures that the media objects contained in a "switch"
   element provide equivalent information. An author knowing that one
   SMIL player will display one alternative of a "switch" and another
   will display a different part can put different information in the
   two parts. While there are legitimate use cases for this, it also
   gives rise to a security consideration: The author can fool viewers
   into thinking that the same information was displayed when in fact it
   was not.

   In addition, all of the security considerations of RFC 3023 also
   apply to SMIL.

7. Normative References

   [1] "Synchronized Multimedia Integration Language (SMIL) 1.0
        Specification", W3C Recommendation REC-smil-19980615,
        http://www.w3.org/TR/1998/REC-smil/, July 1998.

   [2] "Synchronized Multimedia Integration Language (SMIL 2.0) -
        [Second Edition]", W3C Recommendation,
        http://www.w3.org/TR/2005/REC-SMIL2-20050107/, January 2005.

   [3] "Synchronized Multimedia Integration Language (SMIL 2.1)", W3C
        Recommendation, http://www.w3.org/TR/2005/REC-SMIL2-20051213/,
        December 2005.

   [4] Murata, M., St. Laurent, S., and D. Kohn, "XML Media Types", RFC
        3023, January 2001.

8. Informative References

   [5] Baker, M. and P. Stark, "The 'application/xhtml+xml' Media
        Type", RFC 3236, January 2002.

   [6] H. Ohto, J. Hjelm, G. Klyne, M. Butler, L. Tran, F. Reynolds, C.
        Woodrow "Composite Capability/Preferences Profiles (CC/PP):
        Structure and Vocabularies 1.0", W3C Recommendation
        http://www.w3.org/TR/CCPP-struct-vocab/, January 2004.

Author's Address

   Philipp Hoschka
   W3C/ERCIM
   2004, route des Lucioles - B.P. 93
   06902 Sophia Antipolis Cedex
   FRANCE

   EMail: ph@w3.org

Full Copyright Statement

Intellectual Property

   The IETF takes no position regarding the validity or scope of any
   Intellectual Property Rights or other rights that might be claimed to
   pertain to the implementation or use of the technology described in
   this document or the extent to which any license under such rights
   might or might not be available; nor does it represent that it has
   made any independent effort to identify any such rights. Information
   on the procedures with respect to rights in RFC documents can be
   found in BCP 78 and BCP 79.

   Copies of IPR disclosures made to the IETF Secretariat and any
   assurances of licenses to be made available, or the result of an
   attempt made to obtain a general license or permission for the use of
   such proprietary rights by implementers or users of this
   specification can be obtained from the IETF on-line IPR repository at
   http://www.ietf.org/ipr.

   The IETF invites any interested party to bring to its attention any
   copyrights, patents or patent applications, or other proprietary
   rights that may cover technology that may be required to implement
   this standard. Please address the information to the IETF at
   ietf-ipr@ietf.org.

Acknowledgement